

# XCELL XP 7-12

## 12V 7AH (20 HOUR)




### General Features

- Absorbent Glass Mat (AGM) technology for efficient gas recombination of up to 99% and freedom from electrolyte maintenance or water adding.
- Not restricted for air transport-complies with IATA/ICAO Special Provision A67.
- UL-recognized component.
- Can be mounted in any orientation.
- Computer designed lead, calcium tin alloy grid for high power density.
- Long service life, float or cyclic applications.
- Maintenance-free operation.
- Low self discharge.

### Dimensions and Weight

Length(mm / inch).....151 / 5.94  
 Width(mm / inch).....65 / 2.56  
 Height(mm / inch).....93.5 / 3.68  
 Total Height(mm / inch).....100 / 3.94  
 Approx. Weight(Kg / lbs).....2.43 / 5.36



### Performance Characteristics

Nominal Voltage .....12V  
 Number of cell .....6  
 Design Life .....3~5 years  
 Nominal Capacity 77°F(25°C)  
     20 hour rate (0.35A, 10.5V).....7Ah  
     10 hour rate (0.68A, 10.5V).....6.8Ah  
     5 hour rate (1.13A, 10.5V).....5.65Ah  
     1 hour rate (4.56A, 9.6V) .....4.56Ah  
 Internal Resistance  
     Fully Charged battery 77°F(25°C) ..... 28mOhms  
 Self-Discharge  
     3% of capacity declined per month at 20°C(average)  
 Operating Temperature Range  
     Discharge.....-20~60°C  
     Charge .....-10~60°C  
     Storage.....-20~60°C  
 Max. Discharge Current 77°F(25°C) .....105A(5s)  
 Short Circuit Current .....350A  
 Charge Methods: Constant Voltage Charge 77°F(25°C)  
     Cycle use .....14.5-14.9V  
     Maximum charging current ..... 2.8A  
     Temperature compensation .....-30mV/°C  
     Standby use .....13.6-13.8V  
     Temperature compensation .....-20mV/°C

### Discharge Constant Current (Amperes at 77°F25°C)

End Point Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60V	29.1	18.4	14.8	8.30	4.56	1.84	1.26	0.70	0.363
1.65V	27.5	17.5	14.2	7.90	4.40	1.80	1.22	0.69	0.359
1.70V	26.0	16.7	13.6	7.62	4.22	1.74	1.17	0.69	0.355
1.75V	24.4	15.7	13.0	7.24	4.04	1.68	1.13	0.68	0.350
1.80V	22.8	14.8	12.4	7.03	3.84	1.63	1.08	0.66	0.344

### Discharge Constant Power (Watts at 77°F25°C)

End Point Volts/Cell	5min	10min	15min	30min	45min	1h	2h	3h	5h
1.60V	52.0	35.1	27.5	15.2	11.50	8.97	5.06	3.59	2.33
1.65V	49.4	33.3	26.5	14.6	11.00	8.59	4.94	3.50	2.29
1.70V	46.9	31.6	25.4	14.0	10.50	8.23	4.80	3.40	2.25
1.75V	44.5	29.8	24.3	13.4	10.10	7.99	4.65	3.30	2.21
1.80V	41.6	28.0	23.3	12.9	9.75	7.62	4.50	3.19	2.15

(Note)The above characteristics data are average values obtained within three charge/discharge cycles not the minimum values.

# XCELL XP 7-12

## 12V 7AH (20 HOUR)

